

Film	Rév.	Dilution	ASA/ISO	35mm	120	Plan film	Temp
ILFORD							
Pan F+	T-Max	1+4	50	4	4		20C
Pan F+	T-Max	1+9	80	6	6		24C
Pan F+	T-Max	1+4	125	7			20C
FP4+	T-Max	1+4	100	4.5	4.5		20C
FP4+	T-Max	1+4	125	4.5-8	4.5-8	4.5-8	20C
FP4+	T-Max	1+4	125			5.5	20C
FP4+	T-Max	1+4	125	6.5	6.5		20C
FP4+	T-Max	1+9	160	11			24C
FP4+	T-Max	1+4	200	9	9	9	20C
FP4+	T-Max	1+4	320	12			20C
HP5+	T-Max	1+4	125	4.5	4.5		20C
HP5+	T-Max	1+4	400	6.5	6.5	6.5	20C
HP5+	T-Max	1+9	500	15	15	15	24C
HP5+	T-Max	1+4	800	8	8	8	20C
HP5+	T-Max	1+4	1600	9.5	9.5	9.5	20C
HP5+	T-Max	1+4	3200	11.5	11.5	11.5	20C
HP5+	T-Max	1+4	3200	9.5			24C
Delta 100 Pro	T-Max	1+4	50	6	6	6	20C
Delta 100 Pro	T-Max	1+9	80	12	12	12	24C
Delta 100 Pro	T-Max	1+4	100	7	7	7	20C
Delta 100 Pro	T-Max	1+4	200	8	8	8	20C
Delta 400 Pro	T-Max	1+4	200	5	5		20C
Delta 400 Pro	T-Max	1+4	200	4	4		24C
Delta 400 Pro	T-Max	1+4	400	6.5	6.5		20C
Delta 400 Pro	T-Max	1+4	500	7	7		20C
Delta 400 Pro	T-Max	1+4	500	5.5	5.5		24C
Delta 400 Pro	T-Max	1+4	800	8.5	8.5		20C
Delta 400 Pro	T-Max	1+4	800	7	7		24C
Delta 400 Pro	T-Max	1+4	1600	10.5	10.5		20C
Delta 400 Pro	T-Max	1+4	1600	8.5	8.5		24C
Delta 400 Pro	T-Max	1+4	3200	13.5	13.5		20C
Delta 400 Pro	T-Max	1+4	3200	11	11		24C
Delta 3200 Pro	T-Max	1+4	400	5.5	5.5		20C
Delta 3200 Pro	T-Max	1+4	800	6.5	6.5		20C
Delta 3200 Pro	T-Max	1+4	1600	7.5	7.5		20C
Delta 3200 Pro	T-Max	1+4	3200	8.5	8.5		20C
Delta 3200 Pro	T-Max	1+4	6400	11	11		20C
Delta 3200 Pro	T-Max	1+4	12500	14	14		20C
SFX 200	T-Max	1+4	200	8.5	8.5		20C
SFX 200	T-Max	1+4	400	10.5	10.5		20C
SFX 200	T-Max	1+4	800	12.5	12.5		20C
KENTMERE							
Kentmere 100	T-Max	1+4	100	5			20C
Kentmere 400	T-Max	1+4	400	5.5			20C
FUJI							
Neopan 100ss	T-Max	1+4	100	5			20C
Neopan 100ss	T-Max	1+4	200	5.5			20C
Neopan 100ss	T-Max	1+4	400	8.5			20C
Neopan 100 Acros	T-Max	1+4	100	5.5	5.5		20C
Neopan 100 Acros	T-Max	1+9	100		10.5		20C
Neopan 100 Acros	T-Max	1+4	200	8	8		20C
Neopan 400	T-Max	1+4	400	6	6		20C
Neopan 400	T-Max	1+9	640		17		20C
Neopan 400	T-Max	1+9	640	11	11		24C

Neopan 400	T-Max	1+4	800	7.25	7.25		20C
Neopan 400	T-Max	1+9	800		19		20C
Neopan 400	T-Max	1+4	1600	10	10		20C
Neopan 1600	T-Max	1+9	640	6			24C
Neopan 1600	T-Max	1+4	1600	4.5			20C
Neopan 1600	T-Max	1+4	3200	10			20C
KODAK							
Plus-X	T-Max	1+4	125-250	5.75	5.75		20C
Plus-X	T-Max	1+4	125-250	4.25	4.25		24C
Plus-X	T-Max	1+4	500	6.25	6.25		24C
Tri-X 320	T-Max	1+4	320		7.25		20C
Tri-X 320	T-Max	1+4	320		8	8	20C
Tri-X 320	T-Max	1+4	320		5.25		24C
Tri-X 400	T-Max	1+4	320		7.25		20C
Tri-X 400	T-Max	1+4	320		5.25		24C
Tri-X 400	T-Max	1+4	400-800	6	6		20C
Tri-X 400	T-Max	1+4	400	6			20C
Tri-X 400	T-Max	1+4	400	4.75			24C
Tri-X 400	T-Max	1+9	400	10.5	10.5		20C
Tri-X 400	T-Max	1+9	640	11	11		24C
Tri-X 400	T-Max	1+4	1600	10	8.5		20C
Tri-X 400	T-Max	1+4	1600	8.75			20C
Tri-X 400	T-Max	1+4	3200	12	11		24C
TMax 100	T-Max	1+4	100-200	7.5	7.5		20C
TMax 100	T-Max	1+4	100-200	6.25	6.25		24C
TMax 100	T-Max	1+4	100-200	6.5	6.5	6.5	24C
TMax 100	T-Max	1+7	100	10	10		24C
TMax 100	T-Max	1+7	100	9.5	9.5		24C
TMax 100	T-Max	1+9	100		17		20C
TMax 100	T-Max	1+9	100	13.5	13.5		24C
TMax 100	T-Max	1+9	160	13	13	13	24C
TMax 100	T-Max	1+4	400	10	10		24C
TMax 100	T-Max	1+4	400	9	9	9	24C
TMax 100	T-Max	1+4	800	11.75	11.75		24C
TMax 100	T-Max	1+4	800	10.5	10.5	10.5	24C
(NEW) TMax 400	T-Max	1+4	400	5.5	5.5		24C
TMax 400	T-Max	1+4	400-800	7	7	7	20C
TMax 400	T-Max	1+4	400-800	6	6		24C
TMax 400	T-Max	1+7	400	10	10		24C
TMax 400	T-Max	1+9	400		25		18C
TMax 400	T-Max	1+9	400		20		20C
TMax 400	T-Max	1+9	400	15	15		24C
TMax 400	T-Max	1+9	500	14	14	14	24C
TMax 400	T-Max	1+4	800	6	6	6	24C
TMax 400	T-Max	1+4	1600	10	10	10	20C
TMax 400	T-Max	1+4	1600	8	8	8	24C
TMax 400	T-Max	1+4	3200	9.5	9.5	9.5	24C
TMax P3200	T-Max	1+4	400	6.5			24C
TMax P3200	T-Max	1+4	400	6			24C
TMax P3200	T-Max	1+4	800	7.5			24C
TMax P3200	T-Max	1+4	800	6.5			24C
TMax P3200	T-Max	1+7	800	13			24C
TMax P3200	T-Max	1+9	800	19.5			24C
TMax P3200	T-Max	1+9	1280	16			24C
TMax P3200	T-Max	1+4	1600	8			24C
TMax P3200	T-Max	1+4	1600	7			24C
TMax P3200	T-Max	1+4	3200	9.5			24C
TMax P3200	T-Max	1+4	3200	9.5			24C

TMax P3200	T-Max	1+4	6400	11			24C
TMax P3200	T-Max	1+4	6400	11			24C
TMax P3200	T-Max	1+4	12500	12			24C
TMax P3200	T-Max	1+4	12500	12.5			24C
TMax P3200	T-Max	1+4	25000	14			24C
TMax P3200	T-Max	1+4	25000	13.5			24C
Technical Pan	T-Max	1+4	50	4-7	4-7	4-7	24C
Technical Pan	T-Max	1+4	200	6.5			24C
HIE Infrared	T-Max	1+4	n/a	4-8		4-8	24C
HIE Infrared	T-Max	1+4	50	7			20C
HIE Infrared	T-Max	1+4	2000	5			24C